



## **Constant Temperature Shock Metal Bath TRCM-602**

[www.labdistributor.com](http://www.labdistributor.com) | [info@labdistributor.com](mailto:info@labdistributor.com)

## Description

Constant Temperature Shock Metal Bath TRCM-602 has a patented module clamping, pressing method, and a temperature range of 0.1 to 110 °C. It has a blending motion of 2000 rpm, a good blending effect, and a faster speed. It could hold a variety of modules and be used to support program editing and storage. The heating, cooling, and mixing processes are demonstrated.

## Features:

- 2000 rpm ultra-high-speed mixing, improved mixing effect, and faster speed
- Wide temperature adjustment range (0.1 to 110 °C)
- The maximum temperature accuracy (20 to 45 °C) is 0.5 °C
- It can carry a variety of modules
- Assist in the editing and storage of programs
- The temperature correction method is simpler and more convenient
- Patented clamping and pressing method for modules

## Applications:

Constant Temperature Shock Metal Bath TRCM-602 has a patented module clamping, pressing method, and a temperature range of 0.1 to 110 °C. It has a blending motion of 2000 rpm, a good blending effect, and a faster speed. It could hold a variety of modules and be used to support program editing and storage. The heating, cooling, and mixing processes are demonstrated.

## Specifications :

<b>Dimensions L×W×H</b>	186×267×145 mm
<b>Display</b>	LCD
<b>Input Voltage</b>	100 to 120V/220 to 240V, 50Hz/60Hz
<b>Maximum Cooling Rate</b>	5 °/min
<b>Maximum Heating Rate</b>	5.5 °/min
<b>Mixing Diameter</b>	3mm
<b>Power</b>	200 W
<b>Programming</b>	9
<b>Speed Adjustment Range</b>	200 to 2000 rpm
<b>Temperature Control Accuracy [20 To 45°]</b>	± 0.5 °
<b>Temperature Control Range</b>	100 °
<b>Temperature Range</b>	0.1 ° / 100 °
<b>Temperature Uniformity [20 To 45°]</b>	± 0.5 °
<b>Time Setting Range</b>	1min to 99 h 59 min
<b>Working Environment Humidity</b>	0.8
<b>Working Environment Temperature</b>	5 to 40 °



Main Street Kansas City MO 64108, USA  
Email: [info@labdistributor.com](mailto:info@labdistributor.com) | Website: [www.labdistributor.com](http://www.labdistributor.com)