



Ultrasonic Cleaner TRUC-601

www.labdistributor.com | info@labdistributor.com

Description

Ultrasonic Cleaner TRUC-601 has an ultrasonic vibration frequency of interaction composed of high-quality SUS304 stainless steel stampings. It has a 2 L capacity, a heating temperature range of 20 to 80°C and a digital timer with a setting range of 0 to 99 minutes. It does not have a drainage ball valve.

Features:

The intensity of ultrasonic vibration, thoroughly solve the ultrasonic cleaning
Its work-performed tank is made of high-quality SUS304 stainless steel molding
The bladder is made of high-quality steel material, and the cladding is made of aluminum
Electronic timer with a period range of 0 to 99 minutes
The drainage ball valves are installed in drainage systems 6L and higher models

Specifications :

1 Unit Packing	25×25×32 cm 34×25×32 cm
1 Unit Weight	3 Kg
Dimensions	19×17×22 Cm
Drainage	Without
Heating Power	100W
Heating Temperature	20 To 80?
Overall Packing	54×54×65 Cm
Rinse Tank Size	15×14×10 cm
Timer	0 To 99min
Ultrasonic Frequency	28/40khz
Ultrasonic Power	80W
Volume	2 L
Weight	25 Kg



Main Street Kansas City MO 64108, USA
Email: info@labdistributor.com | Website: www.labdistributor.com