



Vertical Air Laminar Flow Cabinet TRVLC-601

www.labdistributor.com | info@labdistributor.com

Description

Vertical Air Laminar Flow Cabinet TRVLC-601 is an airflow-closed bench, designed with a stainless steel working space and a sliding glass door. It is equipped with a UV lamp and a fluorescent lamp. The average wind speed ranges from 0.25 to 0.45 m/s. It has a single-single dimension and comes with a primary filter and a HEPA filter. Intended with a digital display, shows the liquid crystal interference. Its maximum power consumption is 400 W.

Features:

The vertical airflow and closed bench effectively prevent outside gas from entering
The ability to operate the area, as well as the distinctive smell from harming the human body
A wind volume adjustable fan system, a light-touch type switch, and a dual-speed voltage
A regulation device is used to maintain a suitable wind speed in the working area
it uses a super-thin aluminum-frame clapboard-free high-efficiency air filter
? Which shrinks the static-pressure tank to the smallest possible size, reducing the outer case's size
Filters and electric components can be easily exchanged by opening the front cover directly
An LED panel powers it with liquid crystal interference
The work surface is made of stainless steel

Specifications :

Dimension Of Working Area(W1×D1×H1)	700×600×700mm
Half Ventilation Peak Value	? 3?m(XYZ direction)
Illumination	?300LX
Maximum Power Consumption	400W
Noise	?62dB
Number Of Bacteria	?0.5per utensil. Hour (90mm utensil)
Overall Dimension (W×D×H)	860×760×1760mm
Power Supply	AC, 220 V/50Hz
Specification And Number Of Fluorescent Lamp Or UV Lamp Of Ultraviolet Lights	20w×1/ 20w×1
Suited Number	single-single
The Average Wind Speed	0.25 to 0.45m/s



Main Street Kansas City MO 64108, USA
Email: info@labdistributor.com | Website: www.labdistributor.com