



Vertical Air Laminar Flow Cabinet TRVLC-605

www.labdistributor.com | info@labdistributor.com

Description

Vertical Air Laminar Flow Cabinet TRVLC-605 is equipped with a fan system with adjustable airflow at normal wind speeds of 0.25 to 0.45 m / s. It has a single, single dimension. There are HEPA filters and primary filters. With stainless steel, workspace, and glass sliding door. The maximum power consumption is 400W. A digital display panel with a liquid crystal-liquid interface controls the system. Comes with an outlet.

Features:

- The vertical closed worktop effectively prevents outside gas from entering and the weird odor
- It employs a wind volume adjustable fan system
- A light-touch type switch and a dual-speed voltage regulation device to maintain a suitable wind speed in the working area
- The personalized design takes into account all of the user's requirements
- It uses a spring-type sliding door that can be oriented in the desired position
- It is designed to be operated easily
- The front cover can be easily accessible to swap screens and electrical equipment
- The work area is made with stainless steel, resistant to corrosion, and easy to clean
- Having a digital display operates with a liquid crystal interface
- It is having with the HEPA filter and primary filter
- The HEPA filter ensures a clean environment in the work area

Specifications :

Dimension Of Working Area(W1×D1×H1)	880×650×580mm
Half Ventilation Peak Value	? 3?m(XYZ direction)
Illumination	?300LX
Maximum Power Consumption	400W
Noise	?62dB
Number of Bacteria	?0.5per utensil. Hour (90mm utensil)
Overall Dimension (W×D×H)	1040×720×1600mm
Power Supply	AC, 220 V/50Hz
Specification And Number Of Fluorescent lamps Or UV Lamps Of Ultraviolet Lights	8W×1/10 W×1
Suited Number	single-single
The Average Wind Speed	0.25 to 0.45m/s



Main Street Kansas City MO 64108, USA
Email: info@labdistributor.com | Website: www.labdistributor.com